

## Section I - IDENTIFICATION

**TRADE NAME:** AQUA KURE™ - WHITE

**MANUFACTURER:** Lambert Corporation  
20 N. Coburn  
Orlando, FL 32805

**PREPARED BY:** Steve Kuhle

**PREPARATION DATE:** 10/15/2007

**TELEPHONE NUMBER:** (407) 841-2940

**EMERGENCY NUMBER:** (800) 424-9300 - Chemtrec



## Section II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS NUMBER</u>	<u>PEL</u> <u>OSHA (PPM)</u>	<u>TLV:</u> <u>ACGIH (PPM)</u>	<u>OTHER</u> <u>LIMITS</u>
Ethanedial	107-22-2	0.1 mg/m <sup>3</sup>	0.1 mg/m <sup>3</sup>	
Mineral Spirits	64742-88-7	500 ppm	100 ppm	
Polyethylene Glycol	25322-68-3	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	
Ammonia, Anhydrous	7664-41-7	35 mg/m <sup>3</sup>	18 mg/m <sup>3</sup>	
Hydroxyethyl Cellulose	9004-62-0	5 mg/m <sup>3</sup> mmmm	3 mg/m <sup>3</sup>	
Cellulose	9004-34-6	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	
Titanium Dioxide TiO <sub>2</sub>	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	

**GENERAL INFORMATION:** This document supersedes all previous versions. To the best of our knowledge the information contained herein is correct. Lambert Corporation of Florida, Inc. assumes no responsibility for accuracy or completeness. User is responsible for suitability.

HMIS	
Health	1
Flammability	1
Reactivity	0
Personal Protection	E

## Section III - PHYSICAL DATA / CHEMICAL CHARACTERISTICS

<b>Boiling Point</b>	310-405°F	<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	1.0
<b>Vapor Pressure (mm Hg):</b>	2.0	<b>Melting Point</b>	N/A
<b>Vapor Density (AIR=1):</b>	> AIR	<b>Evaporation Rate (Butyl Acetate = 1):</b>	0.12
<b>Solubility in Water:</b>	Slightly Soluble	<b>Appearance and Odor:</b>	Cream-colored resin, Petroleum Odor

## Section IV - FIRE AND EXPLOSION HAZARD DATA

<b>Flash Point (Method Used):</b>	212°F (100°C)	<b>LEL:</b> N/A	<b>UEL:</b> N/A
<b>Flammable Limits:</b>	None		
<b>Extinguishing Media:</b>	DRY CHEMICAL, CARBON DIOXIDE, HALON OR REGULAR FOAM.		
<b>Special Fire Fighting Procedures:</b>	WEAR APPROPRIATE PROTECTIVE EQUIPMENT. STOP SPILL/RELEASE IF IT CAN BE DONE WITHOUT RISK. WATER SPRAY MAY BE USEFUL IN MINIMIZING OR DISPERSING VAPORS & COOLING EQUIPMENT EXPOSED TO HEAT & FLAME.		
<b>Unusual Fire and Explosion Hazards:</b>	N/A		

**Section V - REACTIVITY DATA**

<i>Stability:</i>	<b>STABLE</b>
Incompatibility (Conditions or Materials to Avoid):	STRONG ACIDS OR BASES, OXIDIZING AGENTS & SELECTED AMINES.
Hazardous Decomposition of Byproducts:	CARBON MONOXIDE, CARBON DIOXIDE, SULFUR DIOXIDE & HYDROCARBONS
Hazardous Polymerization:	<b>WILL NOT OCCUR</b>
Conditions to Avoid:	AVOID FREEZING

**Section VI - HEALTH HAZARD DATA***Routes of Entry:*

<i>Eyes:</i>	IRRITANT
<i>Inhalation:</i>	MILD IRRITANT
<i>Skin:</i>	MODERATE IRRITANT
<i>Ingestion:</i>	MILD EXCITATION

*Health Data Comment - Additional:*

PROLONGED & REPEATED SKIN CONTACT MAY CAUSE DERMATITIS. MAY CAUSE DIZZINESS FROM PROLONGED INHALATION. DELIBERATE MISUSE BY INTENTIONALLY INHALING MAY BE HARMFUL OR FATAL

<i>Carcinogenicity:</i>	CLASSIFIED	NONE KNOWN
	NTP:	N/A
	IARC Monographs:	N/A
	OSHA Regulated:	NO

*Signs and Symptoms of Exposure:*

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONALLY INHALING MAY BE HARMFUL OR FATAL.

*Medical Conditions Generally Aggravated by Exposure:*

DERMATITIS, OR PRE-EXISTING RESPIRATORY CONDITIONS.

*Emergency & First Aid Procedures:*

<i>Ingestion:</i>	DO NOT INDUCE VOMITING. CALL DOCTOR IMMEDIATELY. ASPIRATION HAZARD. GIVE NOTHING BY MOUTH BECAUSE MATERIAL CAN ENTER LUNGS & CAUSE SEVERE LUNG DAMAGE. IF POSSIBLE DO NOT LEAVE VICTIM UNATTENDED. FOR ANY PERSISTENT IRRITATION GET MEDICAL HELP.
<i>Eyes:</i>	FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.
<i>Skin:</i>	WASH EXPOSED AREA WITH SOAP AND WATER.
<i>Inhalation:</i>	REMOVE TO FRESH AIR.

**Section VII - PRECAUTIONS FOR SAFE HANDLING AND USE***Steps to be taken in case Material is released or spilled:*

REMOVE SOURCES OF HEAT OR IGNITION. INCLUDING INTERNAL COMBUSTION ENGINES & POWER TOOLS. CLEAN UP SPILL BUT DO NOT FLUSH TO SEWER OR SURFACE WATER. VENTILATE AREA AND AVOID BREATHING VAPORS OR MISTS. DIKE AREA AND ABSORB.

*Waste Disposal Method:*

DISPOSE THROUGH A LICENSED WASTE DISPOSAL COMPANY. FOLLOW FEDERAL, STATE, AND LOCAL REGULATIONS. CONTROLLED BURNING OR APPROVED LANDFILL BURIAL.

*Precautions to be Taken in Handling and Storage:*

STORE IN TIGHTLY CLOSED CONTAINERS IN A COOL, DRY PLACE, KEEP FROM FREEZING.

*Other Precautions:*

KEEP CONTAINERS CLOSED TIGHTLY AND IN AN UPRIGHT POSITION.

**FOR INDUSTRIAL USE ONLY****Section VIII - CONTROL MEASURES**

<i>Respiratory Protection (Type):</i>	USE ADEQUATE VENTILATION. IF EXPOSURE LIMITS ARE EXCEEDED A NIOSH/OSHA APPROVED MASK WITH ORGANIC CANISTER MUST BE USED.
<i>Ventilation: Local Exhaust:</i>	RECOMMENDED
<i>Mechanical (General):</i>	IF NECESSARY
<i>Special:</i>	
<i>Other:</i>	
Protective Clothing:	IMPERVIOUS GLOVES & CLOTHING
Eye Protection:	SAFETY GOGGLES OR SPLASH SHIELD
Other Protective Clothing or Equipment:	WEAR IMPERVIOUS CLOTHING AS NEEDED. SAFETY SHOWER & EYE BATH IN VICINITY IS RECOMMENDED.
Work/Hygienic Practices:	PRACTICE GOOD HOUSEKEEPING AND HYGIENE.