

Section I - IDENTIFICATION

TRADE NAME: FORM RELEASE 88™

MANUFACTURER: Lambert Corporation
20 N. Coburn
Orlando, FL 32805

PREPARED BY: Steve Kuhle

PREPARATION DATE: 10/15/2007

TELEPHONE NUMBER: (407) 841-2940

EMERGENCY NUMBER: (800) 424-9300 - Chemtrec



Section II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS NUMBER</u>	<u>PEL OSHA (PPM)</u>	<u>TLV: ACGIH (PPM)</u>	<u>OTHER LIMITS</u>
Petroleum Distillates	64741-89-5	5 mg/m ³	5 mg/m ³	
Diesel Fuel	68476-34-6	5 mg/m ³	100 mg/m ³	
Napthalene	91-20-3	10 ppm	10 ppm	
Highly-Refined Petroleum Lubricant Oil	64741-88-4	5 mg/m ³	10 mg/m	

GENERAL INFORMATION: This document supersedes all previous versions. To the best of our knowledge the information contained herein is correct. Lambert Corporation of Florida, Inc. assumes no responsibility for accuracy or completeness. User is responsible for suitability.

HMIS	
Health	1
Flammability	2
Reactivity	0
Personal Protection	B

Section III - PHYSICAL DATA / CHEMICAL CHARACTERISTICS

Boiling Point	>340°F(171°C)	Specific Gravity (H₂O = 1):	0.87
Vapor Pressure (mm Hg):	1.6	Melting Point	N/A
Vapor Density (AIR=1):	8	Evaporation Rate (Butyl Acetate = 1):	0.01
Solubility in Water:	Insoluble	Appearance and Odor:	Amber liquid, Petroleum Odor

Section IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 166°F (74°C)

Flammable Limits: In Air by Volume **LEL:** 0.06 **UEL:** 7.5

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY, FOAM.

Special Fire Fighting Procedures: USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. USE A SMOTHERING TECHNIQUE FOR EXTINGUISHING FIRE OF THIS COMBUSTIBLE LIQUID. USE SCBA & WEAR FULL PROTECTIVE CLOTHING. USE NO STREAMS OF WATER THIS WILL ONLY SPREAD THE FLAMES.

Unusual Fire and Explosion Hazards: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (INCLUDING RESIDUE) CAN IGNITE EXPLOSIVELY.

Section V - REACTIVITY DATA

<i>Stability:</i>	STABLE
Incompatibility (Conditions or Materials to Avoid):	STRONG OXIDIZING AGENTS
Hazardous Decomposition of Byproducts:	CARBON MONOXIDE, CARBON DIOXIDE, SULFUR DIOXIDE AND HYDROCARBONS
Hazardous Polymerization:	WILL NOT OCCUR
Conditions to Avoid:	FLAME AND BUILD-UP OF STATIC ELECTRICITY

Section VI - HEALTH HAZARD DATA*Routes of Entry:*

<i>Eyes:</i>	MILD IRRITANT
<i>Inhalation:</i>	IRRITANT TO MUCOUS MEMBRANES & RESPIRATORY TRACT.
<i>Skin:</i>	SLIGHT IRRITANT
<i>Ingestion:</i>	MILD EXCITATION, DO NOT INGEST

Health Data Comment - Additional:

SLIGHT TO MODERATE EYE IRRITANT, MODERATE TO EXTREME SKIN IRRITATION, CAUSING REDNESS, DRYING, DRUMS OR BLISTERING OF SKIN. MAY CAUSE IRRITATION TO MUCOUS MEMBRANES & RESPIRATORY TRACT. PROLONGED EXPOSURE MAY LEAD TO DERMATITIS.

<i>Carcinogenicity:</i>	CLASSIFIED	NO
	NTP:	N/A
	IARC Monographs:	N/A
	OSHA Regulated:	NO

Signs and Symptoms of Exposure:

HEADACHE, DIZZINESS, NAUSEA, VOMITING, LOSS OF COORDINATION, SKIN IRRITATION, WATERY EYES, CONVULSIONS, LOSS OF CONSCIOUSNESS.

Medical Conditions Generally Aggravated by Exposure:

MAY AGGRAVATE PRE-EXISTING DERMATITIS. NIOSH RECOMMENDS THAT DIESEL FUEL BE REGARDED AS A POTENTIAL CARCINOGEN.

Emergency & First Aid Procedures:

<i>Ingestion:</i>	DO NOT INDUCE VOMITING. GET MEDICAL HELP IMMEDIATELY
<i>Eyes:</i>	FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES.
<i>Skin:</i>	COOL EXPOSED AREA IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. IMMEDIATELY WASH AFFECTED AREAS.
<i>Inhalation:</i>	REMOVE TO FRESH AIR.

Section VII - PRECAUTIONS FOR SAFE HANDLING AND USE*Steps to be taken in case Material is released or spilled:*

REMOVE SOURCES OF HEAT OR IGNITION. INCLUDING POWER TOOLS & INTERNAL COMBUSTION ENGINES. CLEAN UP SPILL BUT DO NOT FLUSH TO SEWER OR SURFACE WATER. VENTILATE AREA AND AVOID BREATHING VAPORS OR MISTS.

Waste Disposal Method:

DISPOSE THOROUGH LICENSED WASTE DISPOSAL COMPANY. FOLLOW FEDERAL, STATE, AND LOCAL REGULATIONS. CONTROLLED BURNING OR APPROVED LANDFILL BURIAL.

Precautions to be Taken in Handling and Storage:

STORE IN TIGHTLY CLOSED CONTAINERS IN A COOL DRY PLACE, AWAY FROM SOURCES OF HEAT AND IGNITION. GROUND AND BOND ALL TRANSFER AND STORAGE EQUIPMENT.

Other Precautions:

EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT CUT, WELD, BRAZE, DRILL, GRIND, OR PRESSURIZE. CONTAINERS MAY EXPLODE AND CAUSE SEER INJURY OR DEATH.

FOR INDUSTRIAL USE ONLY**Section VIII - CONTROL MEASURES**

<i>Respiratory Protection (Type):</i>	HIGH VAPORS USE NIOSH/OSHA FULL FACE MASK
<i>Ventilation: Local Exhaust:</i>	RECOMMENDED
<i>Mechanical (General):</i>	RECOMMENDED
<i>Special:</i>	
<i>Other:</i>	
Protective Clothing:	WEAR RESISTANT GLOVES, NITRILE RUBBER.
Eye Protection:	ACRYLIC FACE SHIELD OR GOGGLES WITH SPLASH SHIELD.
Other Protective Clothing or Equipment:	TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WEAR IMPERVIOUS CLOTHING OR BOOTS. HAVE A SAFETY SHOWER AND EYE BATH AVAILABLE.
Work/Hygienic Practices:	PRACTICE GOOD HOUSEKEEPING AND PERSONAL HYGIENE