

Section VI - HEALTH HAZARD DATA*Routes of Entry:*

Eyes: IRRITANT, CONJUNCTIVITIS POSSIBLE WITH LONG TERM EXPOSURE
Inhalation: MILD IRRITANT
Skin: IRRITANT, DERMATITIS POSSIBLE WITH LONG TERM EXPOSURE.
Ingestion: IRRITANT, ULCERS POSSIBLE WITH LONG TERM EXPOSURE

Health Data Comment - Additional:

POSSIBLE BURNS ON EYES, MUCOUS MEMBRANES OF THE UPPER RESPIRATORY AND GASTROINTESTINAL TRACT. OVEREXPOSURE IS AN IRRITANT TO THE SKIN. PROBABLY SLIGHTLY TOXIC BECAUSE OF HIGH ALKALINITY

Carcinogenicity: CLASSIFIED NO
 NTP: N/A
 IARC Monographs: N/A
 OSHA Regulated: NO

Signs and Symptoms of Exposure:

OVEREXPOSURE IS AN IRRITANT TO THE EYES, SKIN, AND RESPIRATORY TRACT. HIGH ALKALINITY OF PRODUCT IS CORROSIVE TO MUCOUS MEMBRANES.

Medical Conditions Generally Aggravated by Exposure:

NO KNOWN EFFECTS ON OTHER ILLNESSES.

Emergency & First Aid Procedures:

Ingestion: DRINK MILK OR WATER, THEN DILUTE VINEGAR. DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY
Eyes: FLUSH EYES & LIDS THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION
Skin: FLUSH SKIN THOROUGHLY WITH WATER.
Inhalation: FLUSH MOUTH AND NASAL PASSAGES THOROUGHLY WITH WATER.

Section VII - PRECAUTIONS FOR SAFE HANDLING AND USE*Steps to be taken in case Material is released or spilled:*

MATERIAL IS SLIPPERY - KEEP PERSONNEL AWAY. ABSORB LIQUID IN SAND OR OTHER ABSORBENT INERT MATERIAL. IF SMALL SPILL, FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER FOR DILUTION.

Waste Disposal Method:

DISPOSE OF IN APPROVED SANITARY LANDFILL OR DILUTE WITH A LARGE VOLUME OF WATER, NEUTRALIZE WITH DILUTE ACID AND FLUSH TO SEWER. OBSERVE ALL FEDERAL, STATE, AND LOCAL REGULATIONS. MUST BE DILUTED WHEN IN GEL STATE AS THIS MAY CAUSE SEWER OBSTRUCTION.

Precautions to be Taken in Handling and Storage:

VERY SLIPPERY WHEN SPILLED. KEEP PERSONNEL AWAY. WASH CONTAMINATED CLOTHING BEFORE RE-USE. IF HANDLED IN BULK, KEEP TRANSFER LINES FLUSHED OUT WITH WATER AND CLOSED WHEN NOT IN USE.

Other Precautions:

NEUTRALIZING CHEMICALS: ANY ACID TO NEUTRALIZE THE HIGH ALKALINITY. ALWAYS DILUTE ACID TO AVOID A VIOLENT REACTION. AVOID CONTACT WITH ZINC, ALUMINUM, LEAD, AND COPPER. STORE AWAY FROM ACIDS. CONTAMINATION OF SOLUTIONS MAY CAUSE GELLING.

FOR INDUSTRIAL USE ONLY

Section VIII - CONTROL MEASURES

<i>Respiratory Protection (Type):</i>	USE NIOSH/OSHA APPROVED RESPIRATOR WHEN WORKING IN MIST FORM.
<i>Ventilation: Local Exhaust:</i>	SHOULD BE ADEQUATE TO REMOVE ANY MIST THAT IS FORMED
<i>Mechanical (General):</i>	NONE
<i>Special:</i>	
<i>Other:</i>	
Protective Clothing:	RUBBER, NEOPRENE, VINYL OR SIMILAR
Eye Protection:	SAFETY GOGGLES IF POSSIBLE SPLASHING CAN OCCUR
Other Protective Clothing or Equipment:	PROTECT ALL SKIN AREAS FROM SPLASHES/CONTACT. HAVE EYEBATH AVAILABLE.
Work/Hygienic Practices:	PRACTICE GOOD HOUSEKEEPING. USE GOOD PERSONAL HYGIENE.